

## BT11RF



<b>Model:</b>	BT 11 RF
<b>Capacity:</b>	61 cu ft R, 4.5 cu ft F
<b>Temperature Range:</b>	R: 1°C to 7°C (33°F to 45°F), F: -18°C to -23°C (0°F to -10°F)
<b>Exterior Dimensions:</b>	68-1/2"h x 24-1/8"w x 24-1/2"d 173cm x 61cm x 62cm
<b>Interior Dimensions:</b>	R: 28"h x 21"w x 20-3/4"d F: 24-3/4"h x 19"w x 18-1/4"d
<b>Doors:</b>	2 each, one each section with locks
<b>Legs:</b>	Leveling legs
<b>Shelves:</b>	R: (2) adjustable wire F: (1) removable wire
<b>Interior Lighting:</b>	No
<b>Insulation: Walls</b>	R: 1-1/4"; F: 2-1/4" non CFC urethane foam in place
<b>Insulation: Door</b>	R: 1-1/4"; F: 2-1/8" non CFC urethane foam in place
<b>Refrigerant:</b>	R134a

<b>Compressor:</b>	(2 each) R: 1; F: 1 / 457 BTU
<b>Condenser:</b>	(2 each) R: 1; F: 1 / fin and tube fan forced air
<b>Air Circulation:</b>	Natural convection evaporator / fan forced air condensers
<b>Refrigerant Control:</b>	Fixed capillary tube
<b>Evaporator:</b>	Aluminum plate-type
<b>Temperature Control:</b>	Electronic with control knob adjustment; dual digital temperature display
<b>Defrost:</b>	R: auto cycle; F: manual
<b>Voltage:</b>	115 / 60 / 1
<b>Export:</b>	Not available
<b>Running Amps:</b>	6.6
<b>Supply Plug:</b>	Single NEMA-5
<b>Shipping: Cubic Feet</b>	34 cu ft
<b>Weight: lbs. domestic</b>	270 lbs., 123 kg
<b>Export:</b>	Not available



*"Manufacturers of Kelvinator Commercial Refrigeration Products"*

563 Corbin Road • Honea Path, SC 29654 • 800-486-8369 • Fax: 864-369-1668  
www.kelvinatorcommercial.com