

NEW MAXIMUM Series

• Solid Door Refrigerator •

Stainless Steel Interior and Front Digitally Controlled Uniform Temperature

* Digitally Controlled Temperature

Enables you to see temperature without opening the door. Freshness of products lasts longer by keeping the correct temperature.

* Efficient Refrigeration System

Turbo Air's solid refrigerators are designed with over-sized evaporators and condensers for faster cooling and greater efficiency.

* Bottom Mounted Compressor

All units feature a bottom-mounted compressor for energy savings, high efficiency and easy service.

The bottom-mounted compressor also allows the food to be placed in an ergonomically correct location.

* High-tech Monitor

The unit will beep to warn you if the door has been open for more than 5 minutes. The monitor digitally display the present temperature.

You can easily adjust the temperature by pressing the up or down button.

* CFC Free

All Turbo Air refrigerators and freezers are foamed in place with high density, close cell, poly-urethane that is CFC free.

* Self-diagnostic System

Shows the status of the unit immediately.

* CEC. California Energy Commission Certificated

* MEA. City of New York Building Department Approved



MSR-23NM



MSR-49NM

Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Weight	L D H	List Price
MSR-23NM	1	23	3	1/3	3.72	264	26.8 x 30.8 x 77.6	3,285.60
MSR-49NM	2	49	6	1/2	7.0	385	53.9 x 30.8 x 77.6	5,046.28

* Height does not include 5" for caster height.

CABINET INTERIOR/EXTERIOR SPECIFICATIONS

ELECTRICAL DATA	MSR-23NM	MSR-49NM
Voltage	115/60-1	115/60-1
Feed Wires (With ground)	3	3
Wattage	550	900
Amperes	3.72 A	7 A
SHIPPING DATA		
Length-Crated (in)	28.3	55.5
Depth-Crated (in)	32.3	32.3
Height-Crated (in)	82.2	82.2
Volume Crated (cu.ft)	43.4	85.2
Net Weight (lbs)	264	385
Weight After Packing (lbs)	290	429
DIMENSIONAL DATA		
# of Doors	1	2
Cubic Feet	23	49
Rack capacity	1	2
Length Overall (in)	26.8	53.9
Depth Overall (in)	30.8	30.8
Height Overall (in)	82.6	82.6
Interior Dimension (LxDxH)	22.9x24.0x59.3	50x24.0x59.3
Shelf Size	22x23.1	24.3x23.1
# of Shelves	3	6

*Design and specifications can be changed without prior notice for product improvement.

- * **Self-contained System**
No plumbing required. Simple installation.
- * **Field Reversible door(MSR-23NM)**
- * **Refrigerator Holds 33°F~38°F**
- * **Bun Tray Racks Available**
All models are available for full door tray racks.
- * **Other Features**
 - Solid and sturdy grill design.
 - Minimum wattage heater in the cabinet frame to conserve energy and keep your cabinet water free.
 - Incandescent interior lighting.
 - Positive seal with self-closing door.
 - Automatic evaporator fan motor delay when the door is open.
 - The defrost systems are time initiated and temperature terminated.
 - 4" swivel casters.(standard)
 - Door locks.
- * **Foamed with polyurethane, high-density cell insulation (CFC free)**

