

Solid Door Refrigerators

**Stainless Steel Interior and Exterior
Digitally Controlled Uniform Temperature**



MSR-23NM



MSR-49NM

FEATURES / BENEFITS

- **DIGITAL TEMPERATURE CONTROL SYSTEM**
Provides precise and constant temperature. This level of precision allows food products to remain fresh over an extended period of time.
- **HIGH-TECH MONITOR**
The unit will beep if the door has been opened for more than 5 minutes. The monitor digitally displays the present temperature and current status of the refrigerator. You can easily change the temperature by adjusting the thermostat.
- **EFFICIENT REFRIGERATION SYSTEM**
Turbo Air's solid door refrigerators are designed with over-sized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.
- **AUTOMATIC EVAPORATOR FAN MOTOR DELAYS**
Through stopping the evaporator fan when the refrigerator door opens, the circulation of hot, moist air into the refrigerator is prevented. This increases energy efficiency and lengthens the life of the compressor.
- **STAINLESS STEEL CABINET CONSTRUCTION**
The Turbo Air New Maximum model boasts a stainless steel interior and exterior (except the back). It guarantees the utmost in cleanliness and long product life. Unlike other companies' products, the sharp corners and edges have been rounded to reduce the risk of injury. The New Maximum can add a touch of style to the most refined setting.
- **ADJUSTABLE, HEAVY DUTY, PE(POLYETHYLENE) COATED WIRE SHELVES**
- **HIGH-DENSITY POLYURETHANE INSULATION**
The entire cabinet structure and solid doors are formed-in-place using high density, CFC free polyurethane insulation.
- **ERGONOMICALLY DESIGNED DOOR**
Customers' fatigue fades away with easy grip handles and doors that open effortlessly. Self-closing and stay open door features make this the ultimate choice in customer convenience.
- **MAGNETIC DOOR GASKET**
Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.
- **BOTTOM MOUNT COMPRESSOR UNITS**
Turbo Air's bottom mount compressor allows easier access for service and extra storage space above. In addition, the lower area provides a cooler and less greasy operating environment which results in reduced compressor running time.
- **REFRIGERATOR HOLDS 33°F ~ 38°F FOR THE BEST IN FOOD PRESERVATION**

Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Crated Weight	L D H
MSR-23NM	1	23	3	1/4	5.5	265	27 x 30 ² / ₃ x 78
MSR-49NM	2	49	6	1/3	9.2	397	54 ² / ₅ x 30 ² / ₃ x 78

* Height does not include 5" for caster height.

MSR-23NM / MSR-49NM SPECIFICATIONS

ELECTRICAL DATA	MSR-23NM	MSR-49NM
Voltage (NEMA-5-15P)	115/60-1	115/60-1
Amperes	5.5 A	9.2 A
Compressor (HP)	1/4	1/3
Feed Wires (with ground)	3	3
Cord Length	6.8 ft.	6.8 ft.
DIMENSIONAL DATA		
# of Doors	1	2
Cubic Feet	23	49
# of Racks Accepted	1	2
Length Overall (in)	27	54 ² / ₅
Depth Overall (in)	30 ² / ₃	30 ² / ₃
Height Overall (in)	78	78
Interior Dimension (LxDxH)	23x24 ⁴ / ₅ x60 ² / ₅	50 ¹ / ₂ x24 ⁴ / ₅ x60 ² / ₅
Shelf Size	21 ³ / ₅ x23 ¹ / ₃	24 ² / ₅ x23 ¹ / ₃
# of Shelves	3	6

*Design and specifications subject to change without notice.

- **WARRANTY :** 1 Year Labor and Parts Warranty
 Additional 4 Years Warranty on Compressor

- **INCANDESCENT INTERIOR LIGHTING**
- **DOOR LOCKS**
- **SELF-CONTAINED SYSTEM**
- **4" SWIVEL CASTERS**
- **SOLID AND STURDY GRILLE DESIGN**
- **LEGS AVAILABLE FOR ALL MODELS (OPTION)**
- **TRAY RACK AVAILABLE (OPTION)**
 All models accept full size tray racks.
- **REMOTE CABINETS AND CONDENSING UNITS AVAILABLE FOR ALL MODELS.**



(unit : inch)

