

NOR-LAKE® SCIENTIFIC

PREMIER PASS-THRU LABORATORY AND PHARMACY REFRIGERATORS


Designed to meet the demanding requirements for scientific and laboratory research. Advanced engineered design incorporates the latest in cabinet, refrigeration, temperature control and monitoring features. Provides energy efficient, convenient, safe and reliable performance for optimal storage temperature environments necessary for a wide range of life science, pharmacy, biological, medical, clinical and industrial applications.

Standard Product Features:

- Digital LED display microprocessor temperature controller
- Audible and visual Hi/Lo temperature alarm
- Adjustable control range from 2°C to 10°C factory preset at 4°C
- Remote alarm contacts
- Continuous product temperature display
- Product sensor with glycerin bottle
- Power supply switch
- Exterior cabinet front, sides and back are painted white
- Exterior cabinet top and bottom are galvanized steel
- Interior cabinet liner and door panels are painted white
- Cabinet and solid doors are foamed-in-place with CFC Free high density polyurethane foam insulation
- Glass door(s) on applicable models are full size, double pane, with frame anti condensate heater wires
- Glass door(s) are standard on all WWF suffix models and WWG suffix models (controller side)
- Solid door(s) on applicable models are full size
- Solid door(s) are standard on WWW suffix models and WWG suffix models (non-controller side)
- Heavy duty door pivot hinges
- Pull door handles
- Magnetic door gaskets
- Centered key door lock(s) (2 keys)
- Four casters on two and four door models (2 locking), Six casters (3 locking) on six door models
- 3 coated wire shelves per door section
- Interior light, switch activated
- Air cooled condensing unit
- Top mounted forced air refrigeration system
- Automatic defrost and condensate evaporation
- Warranties: 18 months parts and labor, 5 year compressor (US and Canada), 18 months parts (International)
- UL/CUL listed
- Tested to meet the Maximum Daily Energy Consumption Requirements (KWhr/day) as defined by the California Energy Commission Appliance Efficiency Regulations and the ENERGY STAR® Program Requirements for Commercial Refrigerators and Freezers.

Optional Features:

- Extra shelf
- Stainless steel two-way drawer (8 maximum per door section)
- Wire basket two-way drawer (6 maximum per door section)
- Access port 2" sleeve with cover
- Sensor access port 1" diameter
- Internal electrical outlet
- Legs in lieu of casters
- Stainless steel interior
- Stainless steel exterior (applicable models)
- Temperature chart recorder with chart paper
- 4-20ma output
- Export crating



NSPT524WWG/



NSPT242WWG/

NSPT524WWG/

NSPT806WWG/

NORLAKE SCIENTIFIC



Committed to our environment



Nor-Lake, Inc.
Registered to ISO 9001:2008
File No. 10001816

NOR-LAKE SCIENTIFIC
A Division of
NOR-LAKE, INCORPORATED
727 Second Street
P.O. Box 248
Hudson, Wisconsin 54016
800-477-5253
715-386-2323
800-388-5253 PARTS
715-386-4290 FAX
www.norlakescientific.com

