

Solid Door Freezers

Exceptional Quality **2 Years Parts and Labor Warranty**



TSF-23SD

TSF-35SD

TSF-49SD

TSF-72SD

FEATURES / BENEFITS

- DIGITAL TEMPERATURE CONTROL SYSTEM**
Provides precise and constant temperature. This level of precision allows food products to remain fresh over an extended period of time.
- HIGH-TECH MONITOR**
The unit will beep if the door has been opened for more than 5 minutes. The monitor digitally displays the present temperature and current status of the freezer. You can easily change the temperature by adjusting the thermostat.
- EFFICIENT REFRIGERATION SYSTEM**
Turbo Air's solid door freezers are designed with oversized and balanced (CFC Free R-404A) refrigeration systems. These include efficient evaporators and condensers for faster freezing and greater efficiency.
- AUTOMATIC EVAPORATOR FAN MOTOR DELAYS**
Through stopping the evaporator fan when the freezer door opens, the circulation of hot, moist air into the freezer is prevented. This increases energy efficiency and lengthens the life of the compressor.
- STAINLESS STEEL CABINET CONSTRUCTION**
The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (except the back). It guarantees the utmost in cleanliness and long product life. Unlike other companies' products, the sharp corners and edges have been rounded to reduce the risk of injury. The Super Deluxe can add a touch of style to the most refined setting.
- STURDY, CLEAN STAINLESS SHELVING**
Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless shelving.
- HIGH-DENSITY POLYURETHANE INSULATION**
The entire cabinet structure and solid doors are formed-in-place using high density, CFC free polyurethane insulation.
- ERGONOMICALLY DESIGNED DOOR**
Customers' fatigue fades away with easy grip handles and doors that open effortlessly. Self-closing and stay open door features make this the ultimate choice in customer convenience.
- MAGNETIC DOOR GASKET**
Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.
- BOTTOM MOUNT COMPRESSOR UNITS**
Turbo Air's bottom mount compressor allows easier access for service and extra storage space above. In addition, the lower area provides a cooler and less greasy operating environment which results in reduced compressor running time.
- FREEZER HOLDS -10°F ~ 0°F FOR THE BEST IN FROZEN FOOD PRESERVATION**

| Model | Swing Door | CU./FT. | #of Shelves | HP | AMPS | Crated Weight | L D H |
|-----------------|------------|-----------|-------------|--------------|-------------|---------------|---------------------------------|
| TSF-23SD | 1 | 23 | 3 | 1/2 | 7.8 | 289 | 27 x 30 1/3 x 78 2/9 |
| TSF-35SD | 2 | 35 | 6 | 1/3 | 10 | 340 | 39 1/2 x 30 1/3 x 78 2/9 |
| TSF-49SD | 2 | 49 | 6 | 3/4 | 10.5 | 463 | 54 2/5 x 30 1/3 x 78 2/9 |
| TSF-72SD | 3 | 72 | 9 | 1 1/4 | 10.4 | 639 | 81 6/7 x 30 1/3 x 78 2/9 |

* Height does not include 5" for caster height.

TSF-23SD / TSF-35SD / TSF-49SD / TSF-72SD SPECIFICATIONS

| ELECTRICAL DATA | TSF-23SD | TSF-35SD | TSF-49SD | TSF-72SD |
|------------------------------------|----------|----------|----------|-------------|
| Voltage (NEMA-5-15P / NEMA-L14-20) | 115/60-1 | 115/60-1 | 115/60-1 | 115/208~230 |
| Amperes | 7.8A | 10A | 10.5A | 10.4A |
| Compressor (HP) | 1/2 | 1/3 | 3/4 | 1 1/4 |
| Feed Wires (with ground) | 3 | 3 | 3 | 4 |
| Cord Length | 8.2 ft. | 8.2 ft. | 8.2 ft. | 9.2 ft. |

**TSF-72SD requires dual voltage 115/208~230V

| DIMENSIONAL DATA | TSF-23SD | TSF-35SD | TSF-49SD | TSF-72SD |
|----------------------------|------------------|------------------|----------------------|------------------|
| # of Doors | 1 | 2 | 2 | 3 |
| Cubic Feet | 23 | 35 | 49 | 72 |
| # of Racks Accepted | 1 | 2 | 2 | 3 |
| Length Overall (in) | 27 | 39 1/2 | 54 2/5 | 81 6/7 |
| Depth Overall (in) | 30 1/3 | 30 1/3 | 30 1/3 | 30 1/3 |
| Height Overall (in) | 78 2/9 | 78 2/9 | 78 2/9 | 78 2/9 |
| Interior Dimension (LxDxH) | 23x24 4/5x60 2/5 | 35x24 4/5x60 2/5 | 50 1/2x24 4/5x60 2/5 | 78x24 4/5x60 2/5 |
| Shelf Size | 21 3/5x23 1/3 | 17 1/3x23 1/3 | 24 2/5x23 1/3 | 24 2/5x23 1/3 |
| # of Shelves | 3 | 6 | 6 | 9 |

- INCANDESCENT INTERIOR LIGHTING
- MINIMUM WATTAGE HEATER IN CABINET FRAME AND DOOR
- SELF-CONTAINED SYSTEM
- 4" SWIVEL CASTERS
- STANDARD BACKGUARD IMPROVES AIRFLOW
- DOOR LOCKS
- SOLID AND STURDY GRILLE DESIGN
- LEGS AVAILABLE FOR ALL MODELS (OPTION)
- TRAY RACK AVAILABLE (OPTION)
All models accept full size tray racks.
- REMOTE CABINETS AND CONDENSING UNITS AVAILABLE FOR ALL MODELS.

*Design and specifications subject to change without notice.

- **WARRANTY :** 2 Years Labor and Parts Warranty
Additional 3 Years Warranty on Compressor

